

## SPECIFICATION FIREWALL

### POWER DEVICE

Nominal Voltage

AC 120/230 V

Frequency Required

50 - 60 Hz

Power Consumption Operational

50 Watt

### NETWORKING

Ports Qty

10

### Features

Intrusion Prevention System (IPS), VPN support, firewall protection, modular design, web threat protection. CAPWAP support, High Availability, IPv4 support, IPv6 support, anti-virus protection, checksum offload support, content filtering, firewall protection, manageable, routing, switching, traffic shaping

### Performance

Firewall throughput (1518-byte UDP): 36 Gbps

Firewall throughput (512-byte UDP): 36 Gbps

Firewall throughput (64-byte UDP): 32 Gbps

Firewall latency (64-byte UDP): 2  $\mu$ s

Firewall throughput: 33 Mpps

VPN throughput (512-bit IPSec): 20 Gbps

VPN throughput (SSL): 5 Gbps

IPS throughput (enterprise traffic mix): 5.2 Gbps

SSL inspection throughput: 6.8 Gbps

Application control (AVC) throughput: 14 Gbps

IPS throughput (optimal traffic mix): 11 Gbps

NGFW throughput: 5 Gbps

CAPWAP throughput: 18 Gbps

Threat protection throughput: 4.7 Gbps

### Data Link Protocol

Ethernet, Fast Ethernet, Gigabit Ethernet

## Capacity

Maximum number of users: unlimited

Concurrent connections: 17500000

## Connectivity Technology

wired

## CHASSIS

### Built-in Devices

status LCD

## POWER

### Max Supported Qty

1

## INTERFACE PROVIDED

Qty

1, 2, 8

## MISCELLANEOUS

### Height (Rack Units)

1 m

## HARD DRIVE

### Installed Qty

1

## ENVIRONMENTAL PARAMETERS

### Min Operating Temperature

32 °F

### Max Operating Temperature

104 °F

## Compatibility

PC

DIMENSIONS & WEIGHT

Width

17.2 in

Depth

11.5 in

Height

1.7 in

Weight

11.46 lbs

EXPANSION SLOTS

Total Qty

1

Free Qty

1

Unified (UTM) Protection

(8x5 Support Care plus Application Control, IPS, AV, Web Filtering and Anti Spam, Sandbox Cloud) 3 yrs (Appliance with Subscription). Bundled with bandwidth monitoring software.