



Bid Notice Abstract

Request for Proposal (RFP)

Reference Number 7156578
Procuring Entity DEVELOPMENT ACADEMY OF THE PHILIPPINES
Title 1 unit Interactive Projector
Area of Delivery Metro Manila

Solicitation Number:	396458	Status	Pending
Trade Agreement:	Implementing Rules and Regulations	Associated Components	1
Procurement Mode:	Negotiated Procurement - Small Value Procurement (Sec. 53.9)	Bid Supplements	0
Classification:	Goods	Document Request List	0
Category:	Audio and Visual Equipment	Date Published	06/08/2020
Approved Budget for the Contract:	PHP 200,000.00	Last Updated / Time	05/08/2020 13:36 PM
Delivery Period:		Closing Date / Time	10/08/2020 10:00 AM
Client Agency:			
Contact Person:	ryan del rosario lucencio admin assistant San Miguel Ave., Pasig City Metro Manila Philippines 1600 63-02-6310921 Ext.119 63-02-6335570 ryanlucencio@yahoo.com		

Description

1 unit Interactive Projector

Ultra Short Throw Interactive, 3,500 Lumens, WXGA

Technical Specs:

Lamp Life

High-efficiency E-TORL lamp lasts up to 5,000 hours in normal mode and up to 10,000 hours in ECO Mode.

HDMI Connectivity

Includes all-digital, HDMI audio and video connection, for HD quality with just one cable

Wireless Ready

Includes a high-speed LAN module for wireless connectivity

Muti-PC Projection and Moderator Function

Connect up to 50 devices over a network, and select up to 4 displays to project simultaneously – great for comparing students' work

Superb Short-throw Performance

Impressive Screen Size at Close Range

Deliver uninterrupted presentations every time with Epson EB-536Wi projector. This projector boasts a throw ratio as low as 0.48, allowing you to project an 80-inch large screen from just 83cm away.

Reduced Shadow Interference & Minimised Glare

The short throw distance also significantly reduces glare on the presenter and shadow interference on the screen, making the viewing experience conducive and comfortable for everyone in the room.

Enhanced Interactivity Features**Interactive Pen**

Enliven your presentations with the projector's interactive function. The interactive pen provided effectively turns your screen into a large drawing board. You can freely annotate on projected content, making your presentations lively and highly engaging. The higher pen accuracy and response speed make drawing as instant as writing with a normal marker pen.

By connecting the projector to a PC via USB cable, you can use the interactive pen like a PC mouse to select and control elements on the screen for greater flexibility.

PC-free Interactive Functionality

Write on the projector screen like a whiteboard, without a PC input source. With this original feature by Epson, you can annotate on screen without any PC connection to create compelling presentations. The PC-free Interactive mode also allows two people to write simultaneously, with two pens operating at the same time for greater interactivity.

Extend your Interactive Reach

Get more out of your Interactive Pen with the Interactive Pen Extension*. With a longer pen, your interactive experience is enhanced as shadow interference is minimised even when the projector is placed on the table.

*Optional accessory

Ease of Set-up

Projector set-up is simply plug-and-play, with a one-time Auto Calibration and Auto Resolution Adjustment. No driver installation is required except for Mac OS users.

On-screen Projector Operation

With on-screen projector operation, you'll be able to easily operate your projector even if the remote control is not close at hand. Perform basic projector operation functions such as power on, source change, volume adjustment and mute, simply by selecting the icons shown on the screen.

Eco-friendly and Cost-efficient**Longer Lamp Life**

With a long lamp life of 10,000 hours in eco-mode, the frequency of costly lamp replacements is reduced, saving you time and money.

Light Optimiser

Save energy consumption and do your part for the environment with the eco-friendly Light Optimiser function. This feature automatically adjusts projection brightness according to image content brightness, giving you power and cost savings. This function can be turned on/off according to your preference.

Flexible Position**Brightness*2:**

White Light Output (Normal/Eco):3,500lm / 2,900lm Colour Light Output:3,500lm

Connectivity:

Network:Wired LAN: RJ45 x 1 (100Mbps)

Wireless: Optional (ELPAP10)Analog Input:D-Sub 15Pin: 2 (Blue)

Composite: RCA x 1 (Yellow)Digital Input:HDMI: 3 (HDMI1 in common with MHL)Output Terminal:D-Sub 15Pin: 1 (Black) In common with Computer2Audio Input:Stereo Mini Jack:3Audio Output:Stereo Mini Jack: 1Control I/O:RS-232C: D-Sub 9pin x 1

Interactive Sync Stereo Mini Jack IN x 1, OUT x 10Others:USB Type A: 1 (for USB Memory, USB Document Camera, Firmware Update, Copy OSD Settings)

USB Type B: 1 (for USB Display, Mouse, K/B, Control, Firmware Update, Interactive, Copy OSD Settings)

Microphone Input: 1

Contrast Ratio:

Contrast Ratio:14,000:1

Wireless Specifications:

Supported Speed for Each Mode:IEEE 802.11b: 11 Mbps*3

IEEE 802.11g: 54 Mbps*3

IEEE 802.11n: 130 Mbps*3Wireless LAN Security:WPA/WPA2-Personal (with optional ELPAP10)

Screen Size (Projected Distance):

Screen Size (Projected Distance):60" - 100" [35.4 - 60.1 cm] 74.3" screen 44.3cm

Operating Temperature:

Operating Temperature:5 - 40 °C <41 - 104 °F> (0m / 0ft - 2,286m / 7,500ft)

5 - 35 °C <41 - 95 °F> (over 2,286m / 7,500ft) (20% - 80% humidity, No Condensation)Multi-projection Use:5 - 35 °C <41 - 95 °F> (0m / 0ft - 2,286m / 7,500ft)

5 - 30 °C <41 - 86 °F> (over 2,286m / 7,500ft) (20% - 80% humidity, No Condensation)

Operating Altitude:

Operating Altitude:0-3,000m <0-9,843 ft> (over 1,500m / 4,921 ft: with High altitude mode)

Start-Up Period:

Start-Up Period:About 8 seconds, Warm-up Period: 30 seconds

Cool Down Period:

Cool Down Period:Instant Off

Internal Speaker(s):

Sound Output:16W Mono

Dimension Excluding Feet (W x H x D):

Dimension Excluding Feet (W x H x D):367 x 149 mm x 400

Weight:

Weight:Approx. 5.8kg

Air Filter:
Type:ElectrostaticFilterMaintenance Cycle*4:5,000 hours (Power Consumption: Normal) 10,000 hours (Power Consumption: Eco)
Fan Noise:
Fan Noise (Normal / Eco / Eco2):35dB / 30dB / 29dB
Power:
Power Supply Voltage:100 - 240 V AC ±10%, 50/60 Hz
Keystone Correction:
Vertical/Horizontal:Vertical / Horizontal (Zoom : Tele): ±3° / ±3°Quick Corner:Yes
Direct Power On / Off:
Direct Power On / Off:Yes
Specifications of Main Parts:
LCD:Size: 0.59" (D9 C2fine)
Native Resolution: WXGALamp:Type: 250W UHE
Life (Normal / Eco / Eco2)*1: 5,000 hours / 10,000 hours / 9,000 hours

Created by ryan del rosario lucencio

Date Created 05/08/2020

The PhilGEPS team is not responsible for any typographical errors or misinformation presented in the system. PhilGEPS only displays information provided for by its clients, and any queries regarding the postings should be directed to the contact person/s of the concerned party.